



7" Intel® Atom™ Z530P Rugged Tablet PC

Features:

- 7" Wide TFT Active Matrix Outdoor-readable Touch Panel
- Ultra Low Power Consumption
- Fully Rugged Mobile POS for Warehousing/Vehicle Computer Application
- Meets MIL-STD-810F, Whole Machine IP54 Grade, Drop Resistant from height of 4ft
- High Mobility, Multi-network Connectivity (Bluetooth/WLAN/HSUPA/3.75G/GPS)
- Multi-identification Devices (Barcode, RFID, MSR)
- Hot-swappable Dual-batteries, Providing Battery Life up to 8 Hours
- 61-key Keypad

Guardian™ Rugged Tablet PC

Model 710

SPECIFICATIONS

Item:	Rugged Tablet PC, Model 710	
System:	CPU Graphics Controller Memory Chipset BIOS Audio Storage	Intel® Atom™ Z530P 1.6GHz CPU with FSB 533MHz GMA 500 Integrated 2GB DDR2-667 SDRAM Intel® System Controller Hub US15WPT AMI BIOS Azalia HD DT Audio 1 x 32GB 1.8" SSD
Peripherals and Devices:	Serial Port USB Port Camera RFID Ethernet Wi-Fi Bluetooth GSM/UMTS Barcode Scanner MSR Expansion SIM Socket	1 x RS-232 port 2 x USB 2.0 ports 1 x 2.0 megapixels CMOS camera Integrated ISO 15693/14443A/14443B RFID Reader (distance: 3~5cm; speed: 5 cards/sec) 1 x Realtek Gigabit Ethernet controller Integrated WLAN 802.11 b/g/n Integrated Bluetooth 2.1 + EDR Up to HSUPA (3.75G) 1 x 1D/2D Barcode scanner 1 x Magnetic Stripe Reader module (optional) 1 x 35-pin pogo connector for connection with vehicle cradle 1 x SIM socket (located underneath the battery pack)
Button & Indicator:	Function Keys Power Button Keypad	6 x Function keys 2 x Menu buttons on the front 2 x Barcode Scanner trigger button on the sides 1 x Power on/off button on the right side 1 x 61-key keypad
LCD Display:	Size/Type Max. Resolution Luminance Contrast Ratio Backlight Type	7" wide active matrix TFT 1024 x 600 (WVGA) w/ 262,144 colors 800 cd/m ² (typ.) 400 : 1 LED
Touch Screen:	Type Light Transparency Controller Interface	Analog Resistive 73% (typ.) USB Interface
Power Supply:	Adapter Input Adapter Output Battery Type Battery Capacity Battery Operating Time	100 ~ 240VAC (Full Range) 19VDC, 3.42A, 65W Li-battery pack 2 x 2600mAH 3-cell 8 hours
Mechanical & Environmental:	Operating Temperature Storage Humidity Dimensions (W x D x H) Gross Weight Vibration Shock Transit Drop IP Rating Regulatory	0 ~ 45°C (32 ~ 113°F) 5 to 95% (non-condensing) 240 x 47 x 188 mm (9.45" x 1.85" x 7.4") 1.7 kg (3.7 lb) 3 Grms/ 5 ~ 500Hz/ random operation 40G peak acceleration (11 ms duration) 122cm (4 feet) drop to wood IP54 compliant CE/FCC Class B compliant

Due to our constant effort to improve products, Industrial Computing Inc. reserves the right to change or modify features and specifications without notice.



260 Bear Hill Road
Waltham, MA 02451

Tel: (781) 890-3111
Fax: (781) 890-7117
www.industcomputing.com