

Industrial Computing

260 Bear Hill Road • Waltham, Massachusetts 02451
Tel. (781) 890-3111 • Fax: (781) 890-7117
www.industcomputing.com

▶ 1U Rackmount TFT LCD monitor keyboard drawer / KVM switch



Panel button controls

- Exit
- Activate On-Screen Display Menu (OSD)
- Adjust control
- Display On/Off

Patent

**KBT-119 &
KBT-119-8 KVM &
KBT-119-16 KVM**

Specification

- Panel: 19" LCD Panel
- Display type: TFT/LCD active matrix color
- Resolution: 1280 x1024
- Contrast ratio: 700: 1 typical
- Brightness: 300 nits
- Panel Color: 16.7 million display colors
- Operating Temp.: 0C - 50C
- Storage Temp.: -20C - 60C
- MTBF: 25000 hours
- Adjustable mounting brackets from 15" to 33"
- Option: USB available
- Dimension: 17.4"(W) x 1.75"(H) x 25.6"(D)

Power Supply

- Remote adapter: 110V ~ 220V AC Input/12V 5A Output
- Adapter size: 4.25"(L) x 2.4"(W) x 1.18"(H)
- Cable length from mains plug to adapter: 71.65"
- Safety approval: UL, CE
- Optional: +12V, +24V, -48V DC Input

Ordering Information

- KBT-119:
1U height, 19" TFT LCD monitor
- KBT-119-8KVM:
1U height, 19" TFT LCD monitor, keyboard, touch Pad with 8 ports KVM switch
- KBT-119-16KVM:
1U height, 19" TFT LCD monitor, keyboard, touch Pad with 16 ports KVM switch